

REGUPOL® AKTIV™ LOK



 **REGUPOL**

REGUPOL.US

ENDURING THE RIGORS, WITH INTERLOCKING, SEAMLESS STYLE

REGUPOL Aktiv™ sports and fitness roll flooring is also available in interlocking tiles. These recycled rubber tiles interlock with a fit so precise, its seams are virtually invisible. Like REGUPOL Aktiv, AktivLok goes well beyond “fitness for purpose” in the selectorized area, the spinning room, the “iron den” – every space in the facility.

Performance. Measured in miles.

Hundreds-of-thousands of miles of AktivLok have been manufactured using state-of-the-art equipment, the cleanest raw materials, and the most consistent color infusion. You get toughness, resiliency, shock absorption, durability, safety, and a virtually seamless appearance.

“Non-permanent” for easy installation and performance.

AktivLok can be loose-laid over almost any sub-floor or finished floor, without permanently bonding to the substrate. Even without bonding, AktivLok stays put until you're ready to remove it or re-lay it. Plus, because it's made of up to 100% post-consumer tire rubber and post-industrial EPDM rubber to the strictest environmental standards, using AktivLok can help qualify your facility for LEED credits.





FLEXIBILITY IS LOCKED IN


REGUPOL AktivLok can be used to create an entire fitness floor in virtually any creative, attractive pattern you can imagine. Or use it in combination with REGUPOL Aktiv roll flooring as a border or other accent treatment.




CORE SERIES




10100
Jet Black




10101
Gray Hound



10102
Jayz Blue



10104
Titan Tan



10105
Firestorm Red



REGUPOL AktivLok

Interlocking Tile Dimensions:

+ 24" x 24" x 3/8"



EDGES

CENTERS

CORNERS

Product Performance Data

| | | |
|-----------------------------------|---|-------------------------|
| Density | ASTM D3676 | 60 pcf – 80 pcf |
| Hardness | ASTM D2240 (Shore A) | 60 +/- 5 |
| Tear Strength | ASTM D624 | 70 pli min – 80 pli min |
| Elongation | ASTM D412 | >145% – 300% |
| Tensile Strength | ASTM D412 | 200 PSI – >220 PSI |
| Flexibility | ASTM F137 1/4" Mandrel | Pass |
| Resistance to Chemicals | ASTM F925 | No change |
| Force Reduction | ASTM F2772 | 12.9% – 13.7% |
| Energy Restitution | ASTM F2772 | 85% – 86% |
| Abrasion Resistance | ASTM D3389 | <1.7g, 1000 cycles |
| Static Load Limit | ASTM F970 | 0.001" @ 250 PSI |
| Coefficient of Friction | ASTM D2047 | >0.95 |
| Slip Resistance | ASTM F2772 | Pass |
| Pill Test | ASTM D2859 | Pass |
| VOC Compliant | ASTM D5116 / CA 1350 | Yes |
| LEED Qualification | Qualifies for Material and Resources Credit | |
| Rolling Load | EN1569 | Pass |
| Resistance to Impact | EN1517 | 14 N/m |
| Resistance to Indentation | EN1516 | 0.1mm |
| Vertical Deformation | ASTM F2772 | 1.4mm |
| Environmental Product Declaration | ISO14025 / UL Environmental | Doc. #: -101047-4150 |



Please feel free to contact us:
 Phone +1 800.537.8737
 Email sales@regupol.com